

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 May 2005 (19.05.2005)

PCT

(10) International Publication Number
WO 2005/043983 A1

(51) International Patent Classification⁷: **A01G 23/083**

(74) Agents: **WALLENGREN, Yngvar et al.**; Patentbyrå Y Wallengren AB, Box 116, S-331 21 Värnamo (SE).

(21) International Application Number:
PCT/SE2004/001520

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 21 October 2004 (21.10.2004)

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:
0302936-0 6 November 2003 (06.11.2003) SE

(71) Applicant (for all designated States except US): **FIBER-PAC KB** [SE/SE]; Bäckåkra, S-340 15 Vittaryd (SE).


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

(72) Inventor; and

(75) Inventor/Applicant (for US only): **LENNARTSSON, Christer** [SE/SE]; Espetuna, S-340 30 Vislanda (SE).

[Continued on next page]

(54) Title: A HARVESTER FOR A FORESTRY MACHINE



(57) Abstract: A harvester (1) for a forestry machine comprises grapples (4, 5), a cutting device (8), trimming devices (6) and advancement means (7) for grasping, cutting, trimming and advancement in the axial direction, respectively, of a tree stem. Further, the harvester (1) includes a measurement device (10) for measuring the length of the tree stem and a measurement device (11) for measuring how the transverse dimension of the tree stem varies along its length. The measurement device (11) includes movable measurement means (14) for contact-free detection of the outer contour of the tree stem, from which the diameter is calculable. The measurement device (11) is located between the trimming device (6) and the advancement means (7) for counteracting dirtying of the measurement device (11). A method of measuring the transverse dimension of a tree stem is disclosed in which the tree stem is moved axially past a measurement device (11) in a harvester (1). The method comprises the steps that a pair of measurement means (14) are moved towards the tree stem, that pairs of read-off values are registered on detection of the outer contour of the tree stem and that the transverse dimension of the tree stem is calculated from each pair of read-off values. After detection of the outer contour, the measurement means (14) are moved a distance away from the tree stem in order thereafter to be once again moved towards the tree stem for a renewed detection of the outer contour. A read-off value which exceeds the previous read-off value is replaced by the previous read-off value before a renewed calculation of the transverse dimension.



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report